

## TECHNICAL DETAILS



Type & Size OD- Outside Dia. ND- Nominal Dia.	Ultimate Breaking Load (KGF)	Safe Pulling Load with Chain Pulley (KGF)	Safe Allowable Hydrostatic Pressure	Safe Total Pump Delivery
			Bar/Kg	Head (mtr.)
<b>OD 113 mm (4") ND: 100 mm</b>				
Medium	6800	4000	10	100
Standard	10000	5900	16	150
Heavy	15900	9350	26	200
Super Heavy	20600	12150	35	350

Type & Size OD- Outside Dia. ND- Nominal Dia.	Ultimate Breaking Load (KGF)	Safe Pulling Load with Chain Pulley (KGF)	Safe Allowable Hydrostatic Pressure	Safe Total Pump Delivery
			Bar/Kg	Head (mtr.)
<b>OD 140 mm (5") ND: 125 mm</b>				
Medium	12200	7750	10	130
Standard	16400	9650	16	160
Heavy	24000	14600	26	230
Super Heavy	30500	18600	35	350

Type & Size OD- Outside Dia. ND- Nominal Dia.	Ultimate Breaking Load (KGF)	Safe Pulling Load with Chain Pulley (KGF)	Safe Allowable Hydrostatic Pressure	Safe Total Pump Delivery
			Bar/Kg	Head (mtr.)
<b>OD 165 mm (6") ND: 150 mm</b>				
Heavy	40000	23500	26	260

